

**3M** Science.  
Applied to Life.™

Safety Series

## Protect tenants and your property even on a budget with 3M™ Safety & Security Window Film.

- ▶ Mitigates hazards from shattered glass due to natural and human causes
- ▶ Increases security and provides added protection against smash and grab burglaries
- ▶ Helps provide protection to people and property from flying glass in natural disasters
- ▶ Increases anti-spall protection for laminated glass
- ▶ Can be combined with 3M™ Impact Protection Attachment Systems for additional safety and security
- ▶ Helps extend the life of furnishings by significantly reducing harmful UV rays, the largest cause of fading

	S40	S70	S80	S140
Break and Entry	★	★★★	★★★	★★★★★
Safety Glazing	★★★	★★★★★	★★★★★	★★★★★
Seismic	★★★★	★★★★★	★★★★★	★★★★★
Blast Mitigation	★	★★★★	★★★★	★★★★
Anti-Graffiti	★★	★★★	★★★	★★★★

Best ★★★★★  
 Better ★★★★  
 Good ★★★  
 Fair ★★  
 Not Recommended ★

Valued Associations and Alliances:



CLINTON CLIMATE INITIATIVE





### Break and Entry

- ▶ Provides precious time by helping to deter unwanted individuals from entering your building or home
- ▶ Help protect occupants and assets

#### Completed Testing

- ▶ EN 356
- ▶ UL 972
- ▶ ULC 332



### Safety Glazing and Human Impact

- ▶ Upgrade your glass to meet safety glazing codes\*
- ▶ Help protect your occupants from broken glass hazards

#### Completed Testing

- ▶ ANSI Z97.1
- ▶ 16 CFR CPSC 1201
- ▶ EN 12600



### Seismic and Spontaneous Glass Breakage

- ▶ Glass fragment retention film for increased protection for people, property and possessions

#### Completed Testing

- ▶ ANSI Z97.1
- ▶ 16 CFR CPSC 1201
- ▶ EN 12600



### Bomb Blast and Explosion Protection

- ▶ Help protect people from flying glass shards, one of the most common causes of blast related injuries and fatalities

#### Completed Testing

- ▶ ASTM F1642
- ▶ GSA TS01-2003
- ▶ ISO 16933

## Film Properties (nominal) — not for specification purposes

Film Type	Film Thickness	Construction	Tensile Strength	Break Strength	Elongation at Break	Peel Strength	Abrasion Resistance
Safety S40	4 mil (0.10mm)	Single ply	25,000 psi (172 MPa)	100 lbs/in (445 N / 25mm)	>125%	> 4 lbs/in (18 N / 25mm)	<5%
Safety S70	7 mil (0.18mm)	Single ply	25,000 psi (172 MPa)	175 lbs/in (778 N / 25mm)	>125%	> 5 lbs/in (22 N / 25mm)	<5%
Safety S80	8 mil (0.20mm)	2-ply	25,000 psi (172 MPa)	200 lbs/in (890 N / 25mm)	>125%	> 2 lbs/in (9 N / 25mm)	<5%
Safety S140	14 mil (0.36mm)	3-ply	25,000 psi (172 MPa)	350 lbs/in (1,557 N / 25mm)	>125%	> 2 lbs/in (9 N / 25mm)	<5%

3M products are tested to multiple industry standards. Glazing systems vary. Contact 3M for more information.

\*Building codes vary, please consult with 3M and your local code official.

**Warranty, Limited Remedy and Disclaimer:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Renewable Energy Division  
3M Center, Building 235-2S-27  
St. Paul, MN 55144-1000  
3M.com/windowfilm

3M is a trademark of 3M.  
Used under license in Canada.

Please recycle. Printed in the U.S.A.  
© 3M 2016. All rights reserved.  
98-0150-0748-1